

KELLY-MOORE PAINT INC -- 1685-SERIES DURA-POXY SEMI-GLOSS ACRYLIC ENAMEL ALL COLORS
-- 8010-00F026084

=====
MSDS Safety Information
=====

FSC: 8010

MSDS Date: 03/05/1990

MSDS Num: BQHKZ

LIIN: 00F026084

Tech Review: 01/21/1993

Product ID: 1685-SERIES DURA-POXY SEMI-GLOSS ACRYLIC ENAMEL ALL COLORS

Responsible Party

Cage: 0Y837

Name: KELLY-MOORE PAINT CO INC

Address: 1015 COMMERCIAL ST

City: SAN CARLOS CA 94070 US

Info Phone Number: 415-592-8337

Preparer's Name: M SCHEFER

=====
Preparer Co. when other than Responsible Party Co.
=====

Cage: 0Y837

Assigned Ind: N

Name: KELLY-MOORE PAINT CO INC

Address: 987 COMMERCIAL ST

City: SAN CARLOS CA 94070

=====
Contractor Summary
=====

Cage: 0Y837

Name: KELLY-MOORE PAINT CO INC

Address: 987 COMMERCIAL ST

City: SAN CARLOS CA 94070 US

Phone: 650-592-8337

=====
Ingredients
=====

Cas: 112-34-5

RTECS #: KJ9100000

Name: 2-(2-BUTOXYETHYOXY)-ETHANOL, DIETHYLENE GLYCOL MONOBUTYL ETHER
(BUTYL CARBITOL)

% by Wt: <5%

Ozone Depleting Chemical: N

Cas: 25265-77-4

RTECS #: UF6000000

Name: PROPANOIC ACID, 2-METHYL, MONOESTER
W/2,2,4-TRIMETHYL-1,3-PENTANEDIOL, TEXANOL (ESTER ALCOHOL)

% by Wt: <5%

Ozone Depleting Chemical: N

 Cas: 107-41-5
 RTECS #: SA0810000
 Name: HEXYLENE GLYCOL, 2-METHYL-2,4-PENTANEDIOL
 % by Wt: <5%
 Other REC Limits: 25 PPM
 OSHA PEL: 25 PPM
 ACGIH TLV: C 21 MG/CUM
 Ozone Depleting Chemical: N

Cas: 4080-31-3
 RTECS #: XX8450000
 Name: 1-(3-CHLOROALLYL)-3,5,7-TRIAZA-1-AZONIAADAMANTANE CHLORIDE, DOWICIL
 100, DOWCO 184
 Ozone Depleting Chemical: N

Name: WEIGHT PER GALLON IN POUNDS: 8-11 LBS

Cas: 13463-67-7
 RTECS #: XR2275000
 Name: TITANIUM DIOXIDE, TIO2
 OSHA PEL: 15 MG/M3 TDUST
 ACGIH TLV: 10 MG/M3 TDUST; 9293
 Ozone Depleting Chemical: N

Name: SILICATES
 =====

Health Hazards Data
 =====

Route Of Entry Inds - Inhalation: YES
 Skin: NO
 Ingestion: NO
 Carcinogenicity Inds - NTP: NO
 IARC: NO
 OSHA: NO
 Effects of Exposure: INHALATION: DIZZINESS, HEADACHE, NAUSEA, CONFUSION,
 UPPER RESPIRATORY TRACT IRRITATION, UNCONSCIOUSNESS. SKIN/EYES:
 IRRITATION.
 Explanation Of Carcinogenicity: NONE
 Medical Cond Aggravated By Exposure: SEE YOUR PHYSICIAN FOR SPECIFIC
 MEDICAL OPINION REGARDING YOUR CONDITION.
 First Aid: INHALATION: REMOVE TO FRESH AIR. RESTORE BREATHING. EYES: WASH
 W/PLENTY OF WATER FOR AT LEAST 15 MINS. SKIN: WIPE OFF W/RAG. WASH
 THOROUGHLY W/SOAP & WATER. INGESTION: OBTAIN MEDICAL ATTENTION IN ALL
 CASES.
 =====

Handling and Disposal
 =====

Spill Release Procedures: VENTILATE AREA TO PREVENT BUILD-UP OF VAPORS.
 FOR SMALL SPILLS: SOAK UP W/ABSORBENT. FOR LARGER SPILLS: DIKE AREA
 W/ABSORBENT MATERIAL & SCOOP UP LIQUIDS.

Waste Disposal Methods: DISCARD IN LAND FILL IN SEALED METAL CONTAINERS AWAY FROM HEAT & FLAME & IN ACCORDANCE W/LOCAL REGULATIONS.

Handling And Storage Precautions: STORE UPRIGHT IN SEALED CONTAINERS AWAY FROM HEAT & FLAME.

Other Precautions: AVOID CONTACT W/SKIN/EYES & CLOTHES. AVOID BREATHING SPRAY MIST OR DUST.

=====
Fire and Explosion Hazard Information
=====

Flash Point Text: >200F

Unusual Fire/Explosion Hazard: CLOSED CONTAINERS MAY EXPLODE (DUE TO BUILD UP OF STEAM PRESSURE) WHEN EXPOSED TO EXTREME HEAT.

=====
Control Measures
=====

Respiratory Protection: USE PARTICLE MASK TO AVOID BREATHING SPRAY MIST OR DUST. USE APPROVED RESPIRATOR FOR ORGANIC VAPOR, SUPPLIED AIR OR SELF-CONTAINED BREATHING EQUIPMENT.

Ventilation: LOCAL EXHAUST TO KEEP BELOW TLV.

Protective Gloves: RECOMMENDED

Eye Protection: GOGGLES OR GLASSES W/SHIELDS

Work Hygienic Practices: REMOVE & WASH CONTAMINATED CLOTHES BEFORE REUSE. WASH HANDS THOROUGHLY AFTER HANDLING.

Supplemental Safety and Health: PRODUCT MAY CONTAIN TITANIUM DIOXIDE OR SILICATES THAT MAY BE NUISANCE DUST HAZARDS IN THEIR ORIGINAL DRY POWDER FORM BUT ARE NOT HAZARDOUS IN WET PAINT.

=====
Physical/Chemical Properties
=====

B.P. Text: 212F

Vapor Density: <1

Evaporation Rate & Reference: SLOWER THAN ETHER

Percent Volatiles by Volume: 62-72%

=====
Reactivity Data
=====

Stability Indicator: YES

Stability Condition To Avoid: HEAT

Materials To Avoid: STRONG OXIDIZING AGENTS

Hazardous Decomposition Products: MAY PRODUCE HAZARDOUS FUMES WHEN HEATED TO DECOMPOSITION AS IN WELDING.

Hazardous Polymerization Indicator: NO

=====
Toxicological Information
=====

=====
Ecological Information
=====

=====
MSDS Transport Information
=====

=====
Regulatory Information
=====

=====
Other Information
=====

=====
HAZCOM Label
=====

Product ID: 1685-SERIES DURA-POXY SEMI-GLOSS ACRYLIC ENAMEL ALL COLORS

Cage: 0Y837

Company Name: KELLY-MOORE PAINT CO INC

Street: 987 COMMERCIAL ST

City: SAN CARLOS CA

Zipcode: 94070 US

Date Of Label Review: 01/21/1993

Label Date: 01/21/1993

Chronic Hazard IND: N

Eye Protection IND: YES

Signal Word: WARNING

Respiratory Protection IND: YES

Health Hazard: Moderate

Contact Hazard: Slight

Fire Hazard: None

Reactivity Hazard: Slight

Hazard And Precautions: INHALATION: DIZZINESS, HEADACHE, NAUSEA,
CONFUSION, UPPER RESPIRATORY TRACT IRRITATION, UNCONSCIOUSNESS.
SKIN/EYES: IRRITATION.

=====
Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.