

KELLY-MOORE PAINT CO INC -- ACRY-LUSTRE ACRYLIC SEMI-GLOSS, 1250-SERIES -- 8010-00N022018

=====
Product Identification
=====

Product ID:ACRY-LUSTRE ACRYLIC SEMI-GLOSS, 1250-SERIES

MSDS Date:12/18/1987

FSC:8010

NIIN:00N022018

MSDS Number: BLSBL

=== Responsible Party ===

Company Name:KELLY-MOORE PAINT CO INC

Address:1015 COMMERCIAL ST

City:SAN CARLOS

State:CA

ZIP:94070

Country:US

Info Phone Num:415-592-8337

Emergency Phone Num:800-424-9300(CHEMTREC)

Preparer's Name:JULIAN SCHAFER

CAGE:KELLY

=== Contractor Identification ===

Company Name:KELLY-MOORE PAINT CO INC

Address:1015 COMMERCIAL ST

City:SAN CARLOS

State:CA

ZIP:94070

Country:US

Phone:415-592-8337

CAGE:KELLY

=====
Composition/Information on Ingredients
=====

Ingred Name:PROPIONIC ACID, 2-METHYL-, MONOESTER

W/2,2,4-TRIMETHYL-1,3-PENTANEDIOL; (TEXANOL). VP: 0.04@68F

CAS:25265-77-4

RTECS #:UF6000000

Fraction by Wt: <5%

Ingred Name:HEXYLENE GLYCOL

CAS:107-41-5

RTECS #:SA0810000

Fraction by Wt: <5%

OSHA PEL:C 25 PPM

ACGIH TLV:C 25 PPM; 9192

=====
Hazards Identification
=====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: DIZZINESS, HEADACHE, NAUSEA,
CONFUSION, IRRITATION TO UPPER RESPIRATORY TRACT, UNCON, SKIN AND
EYE IRRITATION. CHRONIC: NONE KNOWN.

Explanation of Carcinogenicity:NOT RELEVANT.

Effects of Overexposure:SEE HEALTH HAZARDS.

Medical Cond Aggravated by Exposure:SEE YOUR PHYS FOR SPECIFIC MED OPINION REGARDING YOUR CONDITION.

=====
First Aid Measures
=====

First Aid:INHAL: REMOVE TO FRESH AIR. RESTORE BREATHING, CONSULT PHYS.
EYE: FLUSH WITH LARGE VOLUMES OF WATER FOR AT LEAST 15 MIN. GET MED ATTN.
SKIN: WIPE OFF WITH RAG. WASH THOROUGHLY WITH SOAP AND WATER.
INGEST: CONSULT HOSPITAL EMERGENCY ROOM OR POISON CONTROL CENTER IMMEDIATELY.

=====
Fire Fighting Measures
=====

Flash Point:>200F,>93C
Extinguishing Media:NOT APPLICABLE. MEDIA SUITABLE FOR SURROUNDING FIRE
Fire Fighting Procedures:NONE. WEAR NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT.
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE (DUE TO BUILDUP OF STEAM PRESSURE) WHEN EXPOSED TO EXTREME HEAT.

=====
Accidental Release Measures
=====

Spill Release Procedures:VENTILATE AREA TO PREVENT BUILDUP OF VAPORS. FOR SMALL SPILLS, SOAK UP WITH ABSORBANT. FOR LARGE SPILLS, DIKE AREA WITH ABSORBENT MATERIAL AND SCOOP UP LIQUIDS.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE UPRIGHT IN SEALED CONTAINERS AWAY FROM HEAT AND FLAME.
Other Precautions:REMOVE AND WASH CONTAMINATED CLOTHING BEFORE REUSE.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:USE NIOSH/MSHA APPROVED PARTICLE MASK TO AVOID BREATHING SPRAY MIST OR SANDING DUST, IF LOCAL VENT IS ADEQUATE TO KEEP TLV WITHIN ACCEPTABLE LIMITS. IF LOCAL VENT IS NOT ADEQUATE, USE NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC VAPORS SUPPLIED/SCBA IS RECOMMENDED.
Ventilation:LOCAL EXHAUST SUFFICIENT TO KEEP TLV BELOW PRESCRIBED LIMITS.
Protective Gloves:RECOMMENDED.
Eye Protection:CHEMICAL WORKERS GOGGLES.
Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.
Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.
Supplemental Safety and Health
MRF TRADE NAME/PART NO: ALL COLORS.

=====
Physical/Chemical Properties
=====

HCC:N1
Boiling Pt:B.P. Text:212F,100C
Vapor Pressure:SEE INGREDIENTS
Vapor Density: