

MATERIAL SAFETY DATA SHEET

Version Number: 1 Preparation date: 2007-11-05

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: BREAKAWAY MSDS #: MS0127233

Product Code: 6308520, 6308550, 6308110

Recommended use: Floor stripper. This product is intended to be diluted prior to use.

Manufacturer, importer, supplier:

US Headquarters JohnsonDiversey, Inc. 8310 16th St.

Sturtevant, Wisconsin 53177-0902

Ramsey Information Phone: 1-800-421-2768

MSDS Internet Address: www.ramseycompany.com

Emergency telephone number: 1-800-228-5635 (Prosar); 1-651-917-6133 (Int'l Prosar); 01-800-710-3400 (México)

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER

CORROSIVE

CAUSES SKIN AND EYE BURNS

HARMFUL OR FATAL IF SWALLOWED

Principle routes of exposure: Eye contact. Skin contact. Inhalation.

Eye contact: Corrosive. Causes permanent eye damage, including blindness.

Skin contact: Corrosive. Causes permanent damage.

Inhalation: May cause irritation and corrosive effects to nose, throat and respiratory tract.

Ingestion: Corrosive. Causes burns to mouth, throat and stomach.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous ingredients

Ingredient(s)	CAS#	Weight %
Monoethanolamine	141-43-5	10 - 25%
Sodium hydroxide	1310-73-2	1 - 5%
2-butoxyethanol	111-76-2	10 - 25%
Benzyl alcohol	100-51-6	5 - 10%

4. FIRST AID MEASURES

Eye contact: Immediately flush eyes with running water for 15-20 minutes, keeping eyelids open. Get medical

attention immediately.

Skin contact: Immediately flush with plenty of water for 15-20 minutes . Get medical attention immediately.

Inhalation: If breathing is affected, remove to fresh air. Get medical attention immediately.

Ingestion: If swallowed, rinse mouth. Give a cupful of water or milk. THEN IMMEDIATELY CONTACT A

PHYSICIAN OR POISON CENTER. DO NOT induce vomiting unless directed to do so by medical

personnel. Never give anything by mouth to an unconscious person.

Aggravated Medical Conditions: Individuals with chronic respiratory disorders such as asthma, chronic bronchitis, emphysema, etc., may

be more susceptible to irritating effects.

BREAKAWAY 1 of 4

MS0127233 Version Number: 1 Preparation date: 2007-11-05

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media:

The product is not flammable. Extinguish fire using agent suitable for surrounding fire.

Extinguishing media which must not be used for safety reasons:

No information available

Special protective equipment for firefighters:

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear

Specific hazards: Not applicable

Unusual hazards: Corrosive material (See sections 8 and 10).

Specific methods: No special methods required

NFPA Health: 3 Flammability: 0 Instability: 0

6. ACCIDENTAL RELEASE MEASURES

Personal precautions:Use personal protective equipment

Environmental precautionsClean-up methods - large spillage. Soak up with inert absorbent material. Sweep up and shovel into

and clean-up methods: suitable containers for disposal. Use a water rinse for final clean-up.

7. HANDLING AND STORAGE

Handling: Avoid contact with skin, eyes and clothing. Do not taste or swallow. Avoid breathing vapors or mists.

Use only with adequate ventilation. Remove and wash contaminated clothing and footwear before reuse. Wash thoroughly after handling. Product residue may remain on/in empty containers. All precautions for handling the product must be used in handling the empty container and residue. FOR

COMMERCIAL AND INDUSTRIAL USE ONLY.

Storage: Protect from freezing. Keep tightly closed in a dry, cool and well-ventilated place. KEEP OUT OF

REACH OF CHILDREN.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering measures to reduce exposure:

Good general ventilation should be sufficient to control airborne levels. Respiratory protection is not required if good ventilation is maintained.

Personal Protective Equipment

Eye protection: Chemical-splash goggles. **Hand protection:** Chemical-resistant gloves

Skin and body protection: Protective footwear. If major exposure is possible, wear suitable protective clothing and footwear. **Respiratory protection:** In case of insufficient ventilation wear suitable respiratory equipment. A respiratory protection program

that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever

workplace conditions warrant a respirator's use.

Hygiene measures: Handle in accordance with good industrial hygiene and safety practice

Ingredient(s)	ACGIH	OSHA	Mexico	
Monoethanolamine	6 ppm (STEL)	3 ppm (TWA)	6 ppm (STEL)	
	3 ppm (TWA)	6 mg/m³ (TWA)	15 mg/m³ (STEL)	
			3 ppm (TWA)	
			$8 \text{ mg/m}^3 \text{ (TWA)}$	
Sodium hydroxide	2 mg/m³ (Ceiling)	2 mg/m³ (TWA)	2 mg/m³ (Ceiling)	
2-butoxyethanol	20 ppm (TWA)	Skin	75 ppm (STEL)	
		240 mg/m ³ (TWA)	360 mg/m ³ (STEL)	
		50 ppm (TWA)	120 mg/m ³ (TWA)	
			26 nnm (TWA)	

HMIS Health 3 Fire Hazard 0 Reactivity 0

Personal protective equipment

MS0127233 Version Number: 1 Preparation date: 2007-11-05



9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: LiquidAppearance: LiquidColor: Clear ColorlessOdor: Solvent

pH: 13.5

Specific gravity: 1.029

Dilution pH: 13.35 (1:6)
Density: 8.58 lbs/gal

Bulk density: No information availableVapor density: No information availableEvaporation RateNo information availableViscosity: No information available

Solubility: completely soluble

VOC: 30% *
Solubility in other solvents: No information available

Partition coefficient (n-octanol/water): No information available

Boiling point/range:	Not determined		
Melting point/range:	Not determined		
Flash point:	>200°F >93.3°C		
Decomposition temperature:	Not determined		
Autoignition temperature:	No information available		
Elemental Phosphorus:	0 %P		

^{* -} Title 17, California Code of Regulations, Division 3, Chapter 1, Subchapter 8.5, Article 2, Consumer Products, Sections 94508

10. STABILITY AND REACTIVITY

Stability: The product is stable

Polymerization: Hazardous polymerization does not occur

Materials to avoid: Acids. Strong oxidising agents.

Hazardous decomposition products: None reasonably foreseeable.

11. TOXICOLOGICAL INFORMATION

Hazardous ingredients

indu doub ingredient					
Ingredient(s)	LD50 Oral - Rat (mg/kg)	LD50 Dermal - Rabbit	LC50 Inhalation - Rat		
Monoethanolamine	1720	1 mL/kg	Not available		
Sodium hydroxide	140	1350 mg/kg	Not available		
2-butoxyethanol	1400	220 mg/kg	2.21 mg/L (4 h); 450 ppm (4 h)		
Benzyl alcohol	1230	2000 mg/kg	8.8 mg/L (4 h)		

Acute toxicity: Corrosive Oral LD50 estimated to be between 1000 - 2000 mg/kg Dermal LD50 estimated to be > 2000

mg/kg

Chronic toxicity: None known

Specific effects

Carcinogenic effects:

Mutagenic effects:

None known
Reproductive toxicity:

None known
None known
None known
None known

12. ECOLOGICAL INFORMATION

Environmental Information: No data available

13. DISPOSAL CONSIDERATIONS

MS0127233 Version Number: 1 Preparation date: 2007-11-05

13. DISPOSAL CONSIDERATIONS

Waste from residues / unused products:

Dispose of according to all federal, state and local applicable regulations

RCRA Hazard Class: D002

14. TRANSPORT INFORMATION

DOT/TDG: Please refer to the Bill of Lading/receiving documents for up to date shipping information

15. REGULATORY INFORMATION

International Inventories

All components of this product are listed on the following inventories: U.S.A. (TSCA), Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Australia (AICS), Korea (ECL), Japan (ENCS), Philippines (PICCS), New Zealand (NZIoC), China (IECSC).

U.S. Regulations

California Proposition 65: This product is not subject to the reporting requirements under California's Proposition 65

STATE RIGHT TO KNOW

Ingredient(s)	CAS#	MARTK:	NJRTK:	PARTK:	RIRTK:
Monoethanolamine	141-43-5	X	X	X	X
Water	7732-18-5	-	-	-	-
Sodium hydroxide	1310-73-2	X	X	X	X
Sodium xylene sulfonate	1300-72-7	-	-	-	-
2-butoxyethanol	111-76-2	X	X	X	X
Benzyl alcohol	100-51-6	X	X	X	-

CERCLA/ SARA

Ingredient(s)	Weight %	CERCLA/SARA RQ (lbs)	Section 302 TPQ (lbs)	Section 313
Sodium hydroxide 1310-73-2	1 - 5%	1000		
2-butoxyethanol 111-76-2	10 - 25%			X

SARA 311/312 Hazard Categories

Immediate: X
Delayed: Fire: Reactivity: Sudden Release of Pressure: -

Canada

WHMIS hazard class: E Corrosive material.



16. OTHER INFORMATION

Reason for revision: Not applicable

Prepared by: NAPRAC

Additional advice: None

Notice to Reader: This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.