



Garage Door Spray Lubricant

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom2012.

Date of issue: 10/20/2020

Revision date: 10/20/2020

Version: 1.0

SECTION 1: Identification

1.1. Identification

Product name : Garage Door Spray Lubricant
Product code : 16-GDL, 20-GDL, GDL-TS

1.2. Recommended use and restrictions on use

Recommended use : Multi-Purpose Lubricant

1.3. Supplier

The Blaster Corporation
8500 Sweet Valley Drive
Valley View, Ohio 44125 - USA
T (216) 901-5800 - F (216) 901-5801
www.blastercorp.com

1.4. Emergency telephone number

Emergency number : Chemtel 800-255-3924

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Flam. Aerosol 2
Press. Gas (Diss.)
Asp. Tox. 1

2.2. GHS Label elements, including precautionary statements

GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : Flammable aerosol
Contains gas under pressure; may explode if heated
May be fatal if swallowed and enters airways

Precautionary statements (GHS-US) : Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Do not spray on an open flame or other ignition source.
Pressurized container: Do not pierce or burn, even after use.
If swallowed: Immediately call a poison center or doctor
Do NOT induce vomiting.
Store in a well-ventilated place.
Store locked up.
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

Garage Door Spray Lubricant

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

3.2. Mixtures

Name	Product identifier	%
Petroleum distillates, hydrotreated light	(CAS-No.) 64742-47-8	30 - 60
Naphtha (petroleum), heavy alkylate	(CAS-No.) 64741-65-7	15 - 40
Carbon dioxide	(CAS-No.) 124-38-9	1 - 5

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
- First-aid measures after skin contact : If skin irritation occurs: Wash skin with plenty of water. Obtain medical attention if irritation persists.
- First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/effects after inhalation : May cause irritation to the respiratory tract.
- Symptoms/effects after skin contact : May cause skin irritation. Repeated exposure may cause skin dryness or cracking.
- Symptoms/effects after eye contact : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
- Symptoms/effects after ingestion : May be fatal if swallowed and enters airways. May cause gastrointestinal irritation, nausea, vomiting and diarrhea. May result in aspiration into the lungs, causing chemical pneumonia.

4.3. Immediate medical attention and special treatment, if necessary

Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Dry chemical. Carbon dioxide. Halons. Foam.
- Unsuitable extinguishing media : None known.

5.2. Specific hazards arising from the chemical

- Fire hazard : Flammable aerosol. Products of combustion may include, and are not limited to: oxides of carbon. hydrocarbons.
- Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.
- Reactivity : No dangerous reactions known under normal conditions of use.

5.3. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : DO NOT fight fire when fire reaches explosives. Evacuate area.
- Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Vapors may be heavier than air and may travel along the ground to a distant ignition source and flash back. Cool closed containers exposed to fire with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate every possible source of ignition. Use only non-sparking tools. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent entry to sewers and public waters.

Garage Door Spray Lubricant

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

6.3. Methods and material for containment and cleaning up

- For containment : Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.
- Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal. Provide ventilation.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use. Hazardous waste due to potential risk of explosion.
- Precautions for safe handling : Keep away from sources of ignition - No smoking. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not swallow. When using do not eat, drink or smoke. Use only outdoors or in a well-ventilated area. Do not spray on an open flame or other ignition source.
- Hygiene measures : Wash contaminated clothing before reuse. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed.
- Storage conditions : Keep out of the reach of children. Store locked up. Store in a cool, well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Keep in fireproof place.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Petroleum distillates, hydrotreated light (64742-47-8)		
Not applicable		
Naphtha (petroleum), heavy alkylate (64741-65-7)		
Not applicable		
Carbon dioxide (124-38-9)		
ACGIH	ACGIH TWA (ppm)	5000 ppm
ACGIH	ACGIH STEL (ppm)	30000 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	9000 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	5000 ppm
IDLH	US IDLH (ppm)	40000 ppm
NIOSH	NIOSH REL (TWA) (mg/m ³)	9000 mg/m ³
NIOSH	NIOSH REL (TWA) (ppm)	5000 ppm
NIOSH	NIOSH REL (STEL) (mg/m ³)	54000 mg/m ³
NIOSH	NIOSH REL (STEL) (ppm)	30000 ppm

8.2. Appropriate engineering controls

- Appropriate engineering controls : Ensure good ventilation of the work station.
- Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Wear suitable gloves

Eye protection:

Safety glasses or goggles are recommended when using product.

Skin and body protection:

Wear suitable protective clothing

Garage Door Spray Lubricant

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Gas/Pressurized Liquid
Appearance	: Clear
Color	: Colorless
Odor	: Mild aliphatic
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 360 °F
Flash point	: 130 °F [TCC]
Relative evaporation rate (butyl acetate=1)	: > 1
Flammability (solid, gas)	: Flammable aerosol
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: 0.81
Solubility	: Negligible
Partition coefficient n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

Flame projection length	: 0 inches
Heat of combustion	: 46.6 kJ/g
Flashback	: None

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under normal conditions. Flammable aerosol. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Sources of ignition. Heat. Incompatible materials. Direct sunlight. Excessive water.

10.5. Incompatible materials

Strong oxidizing agents. Strong reducing agents.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon. Hydrocarbons.

Garage Door Spray Lubricant

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Petroleum distillates, hydrotreated light (64742-47-8)

LD50 oral rat > 5000 mg/kg

LD50 dermal rabbit > 2000 mg/kg

LC50 inhalation rat > 5.2 mg/l/4h

Naphtha (petroleum), heavy alkylate (64741-65-7)

LD50 oral rat > 7000 mg/kg

LD50 dermal rabbit > 2000 mg/kg

LC50 inhalation rat > 5.04 mg/l/4h

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Not classified

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Specific target organ toxicity – single exposure : Not classified

Specific target organ toxicity – repeated exposure : Not classified

Aspiration hazard : May be fatal if swallowed and enters airways.

Symptoms/effects after inhalation : May cause irritation to the respiratory tract.

Symptoms/effects after skin contact : May cause skin irritation. Repeated exposure may cause skin dryness or cracking.

Symptoms/effects after eye contact : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.

Symptoms/effects after ingestion : May be fatal if swallowed and enters airways. May cause gastrointestinal irritation, nausea, vomiting and diarrhea. May result in aspiration into the lungs, causing chemical pneumonia.

Other information : Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

Petroleum distillates, hydrotreated light (64742-47-8)

LC50 fish 1 45 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])

LC50 fish 2 2.2 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])

Naphtha (petroleum), heavy alkylate (64741-65-7)

EC50 Daphnia 1 2 mg/l (Exposure time: 48 h - Species: Mysisidopsis bahia)

12.2. Persistence and degradability

Garage Door Spray Lubricant

Persistence and degradability : Not established.

12.3. Bioaccumulative potential

Garage Door Spray Lubricant

Bioaccumulative potential : Not established.

Petroleum distillates, hydrotreated light (64742-47-8)

BCF fish 1 61 - 159

Carbon dioxide (124-38-9)

BCF fish 1 (no bioaccumulation)

12.4. Mobility in soil

No additional information available

Garage Door Spray Lubricant

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

12.5. Other adverse effects

Other information : No other effects known.

SECTION 13: Disposal considerations


13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.
Additional information : Flammable vapors may accumulate in the container. Do not incinerate empty containers.

SECTION 14: Transport information

DOT, IATA & IMO

UN-No. : UN1950
Proper Shipping Name : AEROSOLS, flammable, limited quantity
Class : 2.1
Hazard labels :



SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

15.2. International regulations

No additional information available

15.3. US State regulations

No additional information available

SECTION 16: Other information

Date of issue : 10/20/2020
Revision date : 10/20/2020
Other information : None.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.