

ZEP Manufacturing Company Acuity Specialty Products Group, Inc. P.O. Box 2015 Atlanta, GA 30301 1-877-I-BUY-ZEP (428-9937) www.zep.com

Material Safety Data Sheet

and Safe Handling and Disposal Information

HMIS

www.zep.com	Section 1. Chem	ical Product and C	Company Identification	
	Product name		ZEP-ERASE Aerosol Vandal Mark Remover	
	Product Use	Aerosol Vand		
	Product Code	0311		
	Date of issue	05/23/05	Supersedes 03/14/05	
	Emergency For	MSDS Information	n:	
			Specialy Products Group, Inc.	
	Numbers (compliance Services	1-877-I-BUY-ZEP	
	For Medical Emergency:			
		FOTRAC	•	
	(5	877) 541-2016 Toll F	Free - All Calls Recorded	
	Fo	a Transportation I	Emergency:	
	CH	EMTREC		
Printing date: 05/23/05	(800) 424-9300 - All Calls Recorded			
	In the District of Columbia (202) 483-7616			
	Prepared by Compliance Services Group			
	Acuity Specialty Products Group			
	1420 Seaboard Industrial Blvd.			
	Atl	anta, GA 30318		

Name of Hazardous Ingredients	CAS #	% by Weight	Exposure Limits
TETRACHLOROETHYLENE; perchloroethylene; perc; carbon	127-18-4	40 - 50	ACGIH TLV (United States).
pichloride			TWA: 25 ppm 8 hour(s).
OLUENE, aband methoday method barranes talual	108-88-3	20 - 30	STEL: 100 ppm 15 minute(s). ACGIH TLV (United States). Skin
TOLUENE; phenyl methane; methyl benzene; toluol	108-88-5	20 - 30	TWA: 50 ppm 8 hour(s).
			OSHA PEL Z2 (United States).
			TWA: 200 ppm 8 hour(s).
ETHANOL; ethyl alcohol; grain alcohol	64-17-5	10 - 20	ACGIH TLV (United States).
			TWA: 1000 ppm 8 hour(s).
			OSHA PEL (United States).
			TWA: 1000 ppm 8 hour(s).
METHYL ETHYL KETONE; 2-butanone; MEK; methyl acetone	78-93-3	<10	OSHA PEL (United States).
			TWA: 200 ppm 8 hour(s).
			ACGIH / OSHA (United States).
			STEL: 300 ppm 15 minute(s).

Section 3. Hazards Identification

Acute Effect	ts	Routes of Entry Dermal contact. Inhalation. Ingestion.	Health Fire Hererd	3
Skin		age of skin contest (invitant normastor). Skin inflammation is characterized	Fire Hazard Reactivity	3 0
Eyes		rinsed immediately. Effects and symptoms: Irritation, redness, lacrimation,	Personal Protection	В
Inhalation	depression. In limits causes h May cause irri exposure may	case of inhalation (lung irritant). Can cause central nervous system halation of vapor/aerosol concentrations above the recommended exposure leadaches, drowsiness, and nausea, and may lead to unconsciousness or death. tation of respiratory tract, coughing, shortness of breath. Prolonged repeated cause chemical pneumontitis. Medical Conditions Aggravated by Respiratory, Heart (Cardiac).		
	swallowed. 6 data pertains to	ard if swallowed- can enter lungs and cause damage. May be fatal if the product as delivered in the original shipping container(s). Risk of adverse health precautions, including use of proper personal protective equipment.	effects are lessened	by
Carcinogen	ic Effects	Tetrachloroethylene: Classified Group 2A (Probable for human) by IARC, and Anticipated To Be Human Carcinogen by NTP	d Reasonably	
Chronic Eff	ects	The substance may be toxic to kidneys, the nervous system, liver, heart, brain, central nervous system (CNS), ears (hearing impairment/change). Repeated on the substance can produce target organs damage. May cause specific develop See Toxicological Information (section 11)	r prolonged exposur	e to

Product Code 0311

Material Safety Data Sheet

Section 4. Firs	t Aid Measures		
Eye Contact		unning water for at least 15 minutes, keeping eyelids open. Get medical	
-	attention.		
Skin Contact		or mild detergent and water. Remove contaminated clothing and shoes. Get	
hade a local s		evelops. Wash clothing before reuse.	
Inhalation		If not breathing, give artificial respiration. If breathing is difficult, give	
Ingestion	oxygen. Get medical attention	d- can enter lungs and cause damage. Do NOT induce vomiting unless	
ingestion	directed to do so by medical pe	ersonnel. If vomiting occurs, keep head lower than hips to help prevent g by mouth to an unconscious person. Get medical attention immediately.	
Section 5. Fire	Fighting Measures		
Flash Point	Closed cup: Less than 23°C	Flammable Limits Not determined.	
	(73°F). (Tagliabue.)		
Flammability	FLAMMABLE. (CSMA)		
Fire Hazard		VAPOR. Vapor may cause flash fire. Vapors may accumulate	
	May emit toxic fumes under fire	considerable distance to source of ignition and flash back.	
Fire-Fighting		al, carbon dioxide, foam. Wear special protective clothing and	
		ssure, self-contained breathing apparatus. Cool closed	
		exposed to fire with water.	
Section 6. Acc	idental Release Measures		
Spill Clean u		ickaging.	
Section 7. Har	adling and Storage		
		open flame, or any other ignition source. Avoid contact with eyes, skin an	
		ray mists. Use only with adequate ventilation. Watch for accumulation in	
	low confined areas.		
		open flame, or any other ignition source. Keep away from heat and direct	
		l-ventilated area. Do not store above 49°C (120.2°F). Do not puncture or	
	incinerate. Keep out of the reach of chi		
Section 8. Exp	osure Controls, Personal Protect		
Eyes S	Personal Protection plash goggles.	n Protective Clothing (Pictograms)	
•	hemical resistant gloves. (Viton, polyvi	invl sloshol (DVA)	
•		exhaust ventilation or other engineering controls to keep the airborne	
		bective threshold limit value. Wear appropriate respirator when ventilation is	
	nadequate.		
	vsical and Chemical Properties		
Physical State	•	Color Clear. Colorless.	
рН	Not applicable.	Odor Aromatic. Solvent-like. (Strong.)	
Boiling Point	Not determined.	Vapor Pressure 5.9 kPa (44 mmHg) (at 20°C)	
-	ty 0.93 (Water = 1)	Vapor Density Not determined.	
Solubility	Evaporation Rate 1.0 (Carbon tetrachloride)		
,		VOC (Consumer) 49.8% 3.1 (lbs/gal) 373 (g/l)	
Section 10. St	ability and Reactivity		
Stability and			
Incompatibilit	y Avoid contact with str	rong oxidizers, excessive heat, sparks or open flame.	
Hazardous Po			
Hazardous De	-	ioxide, Carbon Monoxide, Hydrogen Chloride (HCl), Chlorine and	
	Phosgene	Gas.	
Section 11. To	xicological Information		
Toxicity to An			
	ORAL (LD50):	Acute: 2629 mg/kg [Rat.].	
	DERMAL (LD50):	Acute: 10000 mg/kg [Rabbit.].	
	Toluene:	A surface 5000 uses (les [D] st]	
	ORAL (LD50): VAPOP (LC50):	Acute: 5000 mg/kg [Rat].	
	VAPOR (LC50): Ethanol:	Acute: 5320 ppm 8 hour(s) [Mouse].	
	ORAL (LD50):	Acute: 7060 mg/kg [Rat].	
		Trans. 7000 mg/ng [run].	

Material Safety Data Sheet

	Material Safety Data Sheet	odder Name Zer-ERASE
Section 12. Ecological In	formation	
-	Not available.	
Biodegradable/OECD	Not available.	
Section 13. Disposal Co	nsiderations	
	ust be disposed of in accordance with federal, Waste Stre l local environmental control regulations.	am Code: D001 Classification: - (Hazardous waste.) Origin: - (RCRA waste.)
Consult your local or region	nal authorities.	
Section 14. Transport Inf	formation	
Proper shipping name	Consumer Commodity	
DOT Classification	ORM-D	UN number Not regulated.
NOTE: DOT classification app the Bill of Lading with your sh	lies to most package sizes. For specific container size classificat ipment.	ions or for size exceptions, refer to
Section 15. Regulatory li	nformation	
U.S. Federal Regulations	S SARA 313 toxic chemical notification and release reporter Tetrachloroethylene Toluene Methyl Ethyl Ketone	rting:
	Clean Water Act (CWA) 311: Tetrachloroethylene; Tol	uene
	Clean air act (CAA) 112 regulated toxic substances: Te Ketone	trachloroethylene; Toluene; Methyl Ethy
	All Components of this product are listed or exempt from	m listing on TSCA inventory.

Section 16. Other Information

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.