

SAFETY DATA SHEET

1. Identification

Product number 80-701
Product identifier GLIDE WHITE LITHIUM GREASE
Company information KIMBALL MIDWEST
4800 ROBERTS RD
COLUMBUS, OH 43228
Company phone 1-800-233-1294
Emergency telephone US 1-800-424-9300 (Chemtrec)
Version # 01
Recommended use LUBRICANT
Recommended restrictions None known.

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1
Gases under pressure Compressed gas
Health hazards Reproductive toxicity (fertility, the unborn child) Category 2
Specific target organ toxicity, single exposure Category 3 narcotic effects
Aspiration hazard Category 1
Environmental hazards Hazardous to the aquatic environment, acute hazard Category 2
Hazardous to the aquatic environment, long-term hazard Category 2
OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. Suspected of damaging fertility. Suspected of damaging the unborn child.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing gas. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

Response If swallowed: Immediately call a poison center/doctor. If inhaled: Remove person to fresh air and keep comfortable for breathing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Do NOT induce vomiting.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information

60.65% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 60.55% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients**Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Distillates (Petroleum), Hydrotreated Heavy Naphthenic		64742-52-5	40 - 60
Distillates (Petroleum), Hydrotreated Light		64742-47-8	20 - 40
Propane		74-98-6	10 - 20
Aliphatic Petroleum Solvent		64742-89-8	2.5 - 10
n-Heptane		142-82-5	2.5 - 10
Zinc Oxide		1314-13-2	1 - 2.5
Cyclohexane		110-82-7	0.1 - 1
Toluene		108-88-3	0.1 - 1
Other components below reportable levels			1 - 2.5

#: This substance has workplace exposure limit(s).

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

Composition comments

The full text for all R-phrases is displayed in Section 16 of the SDS.

4. First-aid measures**Inhalation**

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Call a physician or Poison Control Center immediately. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact

Remove and isolate contaminated clothing and shoes. Immediately flush skin with plenty of water. Call a physician or Poison Control Center immediately. For minor skin contact, avoid spreading material on unaffected skin. Wash clothing separately before reuse.

Eye contact

Call a physician or Poison Control Center immediately.

Ingestion

Call a physician or poison control center immediately. Rinse mouth thoroughly. Never give anything by mouth to a victim who is unconscious or is having convulsions. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Aspiration may cause pulmonary edema and pneumonitis. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

Most important symptoms/effects, acute and delayed

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Aspiration may cause pulmonary edema and pneumonitis.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim warm.

General information

IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures**Suitable extinguishing media**

Alcohol resistant foam. Water fog. Dry chemical powder. Dry chemicals. Carbon dioxide (CO2).

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Contents under pressure. Pressurized container may explode when exposed to heat or flame. Fire may produce irritating, corrosive and/or toxic gases.

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective clothing will only provide limited protection.

Fire-fighting equipment/instructions

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. Some of these materials, if spilled, may evaporate leaving a flammable residue.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. Move container from fire area if it can be done without risk. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.

General fire hazards

Extremely flammable aerosol.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate personal protective equipment. Avoid breathing gas. Emergency personnel need self-contained breathing equipment. Fully encapsulating, vapor protective clothing should be worn for spills and leaks with no fire. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Collect spillage. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS. This material and its container must be disposed of as hazardous waste.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing gas. Avoid prolonged or repeated contact with skin. When using, do not eat, drink or smoke. Do not use in areas without adequate ventilation. Should be handled in closed systems, if possible. Pregnant or breastfeeding women must not handle this product. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Do not empty into drains. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. The pressure in sealed containers can increase under the influence of heat. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Refrigeration recommended. Keep away from food, drink and animal feedingstuffs. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS). Level 3 Aerosol.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Cyclohexane (CAS 110-82-7)	PEL	1050 mg/m3	
n-Heptane (CAS 142-82-5)	PEL	300 ppm 2000 mg/m3 500 ppm	

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Propane (CAS 74-98-6)	PEL	1800 mg/m3 1000 ppm	
Zinc Oxide (CAS 1314-13-2)	PEL	5 mg/m3 5 mg/m3 15 mg/m3	Respirable fraction. Fume. Total dust.

US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Type	Value
Toluene (CAS 108-88-3)	Ceiling TWA	300 ppm 200 ppm

ACGIH

Components	Type	Value
Aliphatic Petroleum Solvent (CAS 64742-89-8)	TWA	400 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Cyclohexane (CAS 110-82-7)	TWA	100 ppm	
n-Heptane (CAS 142-82-5)	STEL TWA	500 ppm 400 ppm	
Toluene (CAS 108-88-3)	TWA	20 ppm	
Zinc Oxide (CAS 1314-13-2)	STEL TWA	10 mg/m3 2 mg/m3	Respirable fraction. Respirable fraction.

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Cyclohexane (CAS 110-82-7)	TWA	1050 mg/m3	
n-Heptane (CAS 142-82-5)	Ceiling TWA	300 ppm 1800 mg/m3 440 ppm 350 mg/m3	
Propane (CAS 74-98-6)	TWA	85 ppm 1800 mg/m3	
Toluene (CAS 108-88-3)	STEL TWA	1000 ppm 560 mg/m3 150 ppm 375 mg/m3	
Zinc Oxide (CAS 1314-13-2)	Ceiling STEL TWA	100 ppm 15 mg/m3 10 mg/m3 5 mg/m3 5 mg/m3	Dust. Fume. Dust. Fume.

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*

* - For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

Toluene (CAS 108-88-3)

Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Toluene (CAS 108-88-3)

Skin designation applies.

Appropriate engineering controls Provide adequate ventilation.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Hand protection Wear appropriate chemical resistant gloves.

Skin protection

Other Wear chemical protective equipment that is specifically recommended by the manufacturer. Use of an impervious apron is recommended. It may provide little or no thermal protection.

Skin protection

Respiratory protection If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using, do not eat, drink or smoke. Do not get in eyes. Do not get this material in contact with skin. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Gas.

Form Aerosol. Compressed gas.

Color Not available.

Odor Not available.

Odor threshold Not available.

pH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling range 178.31 °F (81.29 °C) estimated

Flash point -156.0 °F (-104.4 °C) Propellant estimated

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower (%) 1 % estimated

Flammability limit - upper (%) 8.4 % estimated

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 55.08 psig @70F estimated

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature 432.84 °F (222.69 °C) estimated

Decomposition temperature Not available.

Viscosity Not available.

Other information

Specific gravity 0.36 estimated

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Risk of explosion. Risk of ignition.

Possibility of hazardous reactions Hazardous polymerization does not occur.

Conditions to avoid Heat, flames and sparks. Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition products No hazardous decomposition products are known.

11. Toxicological information**Information on likely routes of exposure**

Ingestion May be fatal if swallowed and enters airways. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Inhalation May be fatal if swallowed and enters airways. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Narcotic effects.

Skin contact No adverse effects due to skin contact are expected.

Eye contact Direct contact with eyes may cause temporary irritation.

Symptoms related to the physical, chemical and toxicological characteristics Aspiration may cause pulmonary edema and pneumonitis. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways. Narcotic effects.

Product	Species	Test Results
11 OZ KIMBALL GLIDE WHT LITH GRS LB 12PK (CAS Mixture)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	5347.5947 ml/kg, 4 Hours estimated 1350.325 mg/kg, 24 Hours estimated
	Rat	2507.4163 mg/kg estimated
<i>Inhalation</i>		
LC100	Cat	600 % estimated
LC50	Mouse	8246.667 mg/l, 120 Minutes estimated 346.6667 %, 120 Minutes estimated 106.6667 mm/l, 2 Hours estimated
	Rat	75651.7344 ppm, 4 Hours estimated 3.7065 mg/l, 4 Hours estimated 3.5839 mg/l/4h estimated
<i>Oral</i>		
LD50	Rat	25668.4492 ml/kg estimated 13197.7891 mg/kg estimated
	Wistar rat	52406.418 g/kg estimated
Components	Species	Test Results

Aliphatic Petroleum Solvent (CAS 64742-89-8)

Acute*Dermal*

LD50 Rabbit > 1900 mg/kg, 24 Hours

Components	Species	Test Results
<i>Inhalation</i> LC50	Rat	> 5020 mg/m3, 4 Hours > 4980 mg/m3 > 4980 mg/m3, 4 Hours > 4.96 mg/l, 4 Hours
<i>Oral</i> LD50	Rat	4820 mg/kg
Cyclohexane (CAS 110-82-7)		
Acute		
<i>Dermal</i> LD50	Rabbit	> 2000 mg/kg
<i>Inhalation</i> LC50	Rat	> 32880 mg/m3, 4 Hours > 5540 ppm, 4 Hours
Distillates (Petroleum), Hydrotreated Heavy Naphthenic (CAS 64742-52-5)		
Acute		
<i>Dermal</i> LD50	Rabbit	> 2000 mg/kg > 2000 mg/kg, 24 Hours
<i>Inhalation</i> LC50	Rat	2.18 mg/l, 4 Hours
<i>Oral</i> LD50	Rat	5000 mg/kg
Distillates (Petroleum), Hydrotreated Light (CAS 64742-47-8)		
Acute		
<i>Dermal</i> LD50	Rabbit	> 2000 mg/kg > 2000 mg/kg, 24 Hours
<i>Inhalation</i> LC50	Rat	> 7.5 mg/l, 6 Hours > 4.6 mg/l, 4 Hours
<i>Oral</i> LD50	Rat	> 5000 mg/kg
n-Heptane (CAS 142-82-5)		
Acute		
<i>Dermal</i> LD50	Rabbit	> 2000 mg/kg, 24 Hours
<i>Inhalation</i> LC50	Rat	> 29.29 mg/l, 4 Hours
Propane (CAS 74-98-6)		
Acute		
<i>Inhalation</i> LC50	Mouse	1237 mg/l, 120 Minutes 52 %, 120 Minutes
	Rat	1355 mg/l 658 mg/l/4h

Components	Species	Test Results
Toluene (CAS 108-88-3)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 5000 mg/kg, 24 Hours
<i>Inhalation</i>		
LC50	Mouse	6405 - 7436 ppm, 6 Hours 5320 ppm, 8 Hours
	Rat	5879 - 6281 ppm, 6 Hours 12.5 - 28.8 mg/l, 4 Hours
<i>Oral</i>		
LD50	Rat	5000 mg/kg
Zinc Oxide (CAS 1314-13-2)		
Acute		
<i>Inhalation</i>		
LC50	Rat	> 5700 mg/m3
<i>Oral</i>		
LD50	Mouse	2000 - 5000 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.
Respiratory or skin sensitization	
Respiratory sensitization	Not available.
Skin sensitization	This product is not expected to cause skin sensitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.
IARC Monographs. Overall Evaluation of Carcinogenicity	
Toluene (CAS 108-88-3)	3 Not classifiable as to carcinogenicity to humans.
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)	
Not listed.	
Reproductive toxicity	Suspected of damaging the unborn child. Suspected of damaging fertility.
Specific target organ toxicity - single exposure	Narcotic effects. May cause drowsiness and dizziness.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	May be fatal if swallowed and enters airways.

12. Ecological information

Ecotoxicity	Toxic to aquatic life with long lasting effects. Accumulation in aquatic organisms is expected.		
Product	Species		Test Results
11 OZ KIMBALL GLIDE WHT LITH GRS LB 12PK (CAS Mixture)			
Aquatic			
Algae	IC50	Algae	50256 mg/L, 72 Hours
Crustacea	EC50	Daphnia	2478 mg/L, 48 Hours
Fish	LC50	Fish	134 mg/L, 96 Hours
Components	Species		Test Results
Aliphatic Petroleum Solvent (CAS 64742-89-8)			
Aquatic			
Algae	IC50	Algae	4700 mg/L, 72 Hours

Components	Species	Test Results
Cyclohexane (CAS 110-82-7)		
Aquatic		
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>) 23.03 - 42.07 mg/l, 96 hours
Distillates (Petroleum), Hydrotreated Light (CAS 64742-47-8)		
Aquatic		
Fish	LC50	Rainbow trout,donaldson trout (<i>Oncorhynchus mykiss</i>) 2.9 mg/l, 96 hours
n-Heptane (CAS 142-82-5)		
Aquatic		
Fish	LC50	Mozambique tilapia (<i>Tilapia mossambica</i>) 375 mg/l, 96 hours
Toluene (CAS 108-88-3)		
Aquatic		
Algae	IC50	Algae 433.0001 mg/L, 72 Hours
Crustacea	EC50	Daphnia 7.645 mg/L, 48 Hours
		Water flea (<i>Daphnia magna</i>) 5.46 - 9.83 mg/l, 48 hours
Fish	LC50	Coho salmon,silver salmon (<i>Oncorhynchus kisutch</i>) 8.11 mg/l, 96 hours
Zinc Oxide (CAS 1314-13-2)		
Aquatic		
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>) 2246 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

Cyclohexane	3.44
n-Heptane	4.66
Propane	2.36
Toluene	2.73

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Consult authorities before disposal. Contents under pressure. Do not puncture, incinerate or crush. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

US RCRA Hazardous Waste U List: Reference

Cyclohexane (CAS 110-82-7)	U056
Toluene (CAS 108-88-3)	U220

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

14. Transport information

DOT

UN number UN1950

UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

IATA

UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	Yes
ERG Code	10L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed.
Cargo aircraft only	Allowed.
Packaging Exceptions	LTD QTY

IMDG

UN number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	Yes
EmS	F-D, S-U
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Packaging Exceptions	LTD QTY
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.


DOT



IATA; IMDG



Marine pollutant



General information

IMDG Regulated Marine Pollutant.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
All components are on the U.S. EPA TSCA Inventory List.

CERCLA/SARA Hazardous Substances - Not applicable.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Cyclohexane (CAS 110-82-7)

Listed.

Toluene (CAS 108-88-3)

Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - Yes
Pressure Hazard - Yes
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Cyclohexane	110-82-7	0.1 - 1
Toluene	108-88-3	0.1 - 1

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Toluene (CAS 108-88-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Propane (CAS 74-98-6)

Safe Drinking Water Act (SDWA) Not regulated.**Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number**

Toluene (CAS 108-88-3) 6594

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Toluene (CAS 108-88-3) 35 %WV

DEA Exempt Chemical Mixtures Code Number

Toluene (CAS 108-88-3) 594

US state regulations**US. Massachusetts RTK - Substance List**

Cyclohexane (CAS 110-82-7)

n-Heptane (CAS 142-82-5)

Propane (CAS 74-98-6)

Toluene (CAS 108-88-3)

Zinc Oxide (CAS 1314-13-2)

US. New Jersey Worker and Community Right-to-Know Act

Cyclohexane (CAS 110-82-7)

n-Heptane (CAS 142-82-5)

Propane (CAS 74-98-6)

Toluene (CAS 108-88-3)

Zinc Oxide (CAS 1314-13-2)

US. Pennsylvania Worker and Community Right-to-Know Law

Cyclohexane (CAS 110-82-7)

n-Heptane (CAS 142-82-5)

Propane (CAS 74-98-6)

Toluene (CAS 108-88-3)

Zinc Oxide (CAS 1314-13-2)

US. Rhode Island RTK

Cyclohexane (CAS 110-82-7)

Propane (CAS 74-98-6)

Toluene (CAS 108-88-3)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Developmental toxin

Toluene (CAS 108-88-3) Listed: January 1, 1991

US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

Toluene (CAS 108-88-3) Listed: August 7, 2009

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No

Country(s) or region	Inventory name	On inventory (yes/no)*
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 08-29-2014

Version # 01

Disclaimer Sprayway cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.