

Material Safety Data Sheet

VANDAL MARK REMOVER #275

Quick Identifier (In Plant Common Name)

Manufacturer's Name & Address
APOLLO INDUSTRIES, INC.
 1850 S. Cobb Industrial Blvd.
 Smyrna, GA 30082

Emergency Telephone No.
 (770) 433-0210 Mon. - Fri. 8-5
 (800) 255-3924 24 HOURS


Date Prepared: November 15, 2000

HMIS Symbol:

Health	2
Flammability	4
Reactivity	0

HMIS— NFPA
 Minimal - 0 - Insignificant
 Slight - 1 - Slight
 Moderate - 2 - Moderate
 Serious - 3 - High
 Severe - 4 - Extreme

NFPA Symbol:



Prepared By:

Checked By:

SECTION 1 - IDENTITY

Common Name: (used on label) Vandal Mark Remover #275
 (Trade name & Synonyms)

Chemical Name Mixture packaged in pressurized aerosol spray can.

SECTION 2 - HAZARDOUS INGREDIENTS

Principal Hazardous Component(s)	CAS No.	OSHA PEL	ACGIH TLV	Other Limits
Propane	74-98-6	1,000 ppm	Not Est.	
Butane	106-97-8	Not Est.	800 ppm	
*Toluene (1)	108-88-3	200 ppm	100 ppm	
Diacetone Alcohol	123-42-2	50 ppm	50 ppm	
*Methyl Ethyl Ketone	78-93-3	200 ppm	200 ppm	300 ppm (STEL)

(1) Warning: This product contains a chemical(s) known to the State of California to cause cancer and reproductive harm.

*Section 313 Supplier Notification - Indicates hazardous ingredients which are toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372.

SECTION 3 - PHYSICAL & CHEMICAL CHARACTERISTICS

Boiling Point	Not Established	Specific Gravity (H ₂ O=1)	0.98	Vapor Pressure (PSI)	70
Volatile Organic Content (% Weight)	98%	Evaporation Rate (BuAc=1)	Faster	pH	N/A
Solubility In Water	20%	Appearance and Odor	Clear liquid, solvent odor		

SECTION 4 - FIRE & EXPLOSION DATA

Flammability (per flame projection)	Extremely Flammable	Flammable Limits in Air % by Volume	Lower Not Est.	Upper Not Est.	Extinguisher Media	Foam, Dry Chemical, CO ₂
-------------------------------------	---------------------	-------------------------------------	----------------	----------------	--------------------	-------------------------------------

Special Fire Fighting Procedures Keep containers cool using water spray. Use proper equipment to protect personnel from bursting containers.

Unusual Fire and Explosion Hazards Contents under pressure. Do not expose to temperatures exceeding 120°F. as containers may vent, rupture or burst.

SECTION 5 - PHYSICAL HAZARDS

Stability	Unstable ☐ Stable ☒	Conditions to Avoid	Open Flames; Temp. > 120°F.	Hazardous Polymerization	May Occur Will not Occur	Conditions to Avoid	None
-----------	--	---------------------	-----------------------------	--------------------------	--------------------------	---------------------	------

Incompatibility (Materials to Avoid) Strong oxidizers, strong alkalis, strong mineral acids.

Hazardous Decomposition Products CO, CO₂, various hydrocarbons.

98725

SECTION 6 - HEALTH HAZARDS

Routes of Entry Inhalation: Yes Eyes / Skin: Yes Ingestion: Unlikely

Signs and Symptoms of Exposure (Acute & Chronic) May cause skin and eye irritation. Ingestion or inhalation at high concentrations may cause nausea, dizziness and headaches.

Medical Conditions Generally Aggravated by Exposure May aggravate lung, liver and kidney disorders.

Chemical Listed as Carcinogen or Potential Carcinogen	National Toxicology Program	Yes ☐ No ☒	I.A.R.C. Monographs	Yes ☐ No ☒	OSHA	Yes ☐ No ☒
---	-----------------------------	--	---------------------	--	------	--

Emergency and First Aid Procedures

1. Inhalation Remove victim to fresh air. Apply artificial respiration if necessary.
Get medical attention.

2. Eyes Flush eyes with water for at least 15 minutes. Get medical attention if irritation persists.

3. Skin Wash affected areas w/ soap & water. Get medical attention if irritation persists.

4. Ingestion Do not induce vomiting. Get medical attention immediately.

SECTION 7 - SPECIAL PROTECTION INFORMATION

Respiratory Protection (Specify Type) None required for normal use.

Ventilation	Local Exhaust	Maintain adequate ventilation	Mechanical (General)	N/A	Special	N/A	Other	N/A
-------------	---------------	-------------------------------	----------------------	-----	---------	-----	-------	-----

Protective Gloves	Wear gloves if contact causes skin irritation.	Eye Protection	Wear safety glasses or goggles.
-------------------	--	----------------	---------------------------------

Other Protective Clothing or Equipment None required.

SECTION 8 - SPECIAL PRECAUTIONS AND SPILL/LEAK PROCEDURES

Precautions to be Taken Handling and Storage Do not store at temperatures above 120°F. Do not puncture or incinerate containers. Keep out of reach of children.

Other Precautions Read label precautions carefully.

Steps to be Taken in Case Material is Released or Spilled Soak up spilled liquid with absorbent material. Place in closed drum for proper disposal.

Waste Disposal Methods Dispose of in accordance with local, state, and federal regulations.

We believe all information given is accurate. It is offered in good faith, but without guarantee. Since conditions are beyond our control, user assumes all responsibility and risk.