



GLIDDEN™ SPRED®
Interior Latex Flat Paint
SP34XX

FINISHES
PAINTING (09900)
9

DESCRIPTION

GLIDDEN™ SPRED® interior flat paint is ideal for dining and bedrooms because of the smooth finish, excellent coverage and great hiding. To keep your painted surface looking great, simply use common household cleaners to wipe away dirt or stains.

SPECIFICATION DATA

Color:

White, ready mix & custom colors

Finish:

Flat, 2-5 units @ 85°

Clean-up Solvent:

Soap & water

Density:

11.02 lbs/gal (1.32 kg/L)

VOC:

0.32 lbs/gal (39 g/L) Maximum

Solids:

Volume - 32% +/- 1%

Weight - 49% +/- 1%

Practical Coverage:

Apply at 400 sq ft/gal (10 m²/L).

Actual coverage may vary depending on substrate and application method.

Flame Spread Rating:

Class A (0-25) over non-combustible surfaces

Flash Point:

None

Dry Time 77°F (25°C) & 50% RH:

To touch - 30 minutes

To recoat - 2-4 hours

Shelf Life:

1 year minimum - unopened

FEATURES

- Hides minor surface imperfections
- Spatter free
- Easy to apply

COMPOSITION

- Vinyl-Acrylic Resin
- Titanium Dioxide and Extender Pigments
- Not manufactured with lead or mercury containing materials.



9 FINISHES
PAINTING (09900)

SURFACE PREPARATION

Spackle holes or cracks • Lightly sand glossy areas.

Make sure all areas are clean, sound and free of flaking paint or any substances such as oil, grease, dirt...anything that will get between your walls and your paint. Prepare *Previously Painted Surfaces* with a **GLIDDEN** primer.

IT IS TIME TO PRIME - PREPARING UNPAINTED SURFACES

WALLBOARD - Joint compound must dry for two days before you apply a **GLIDDEN** primer.

WOOD - Sand lightly to a smooth surface, then prime with a **GLIDDEN** primer.

CONCRETE, PLASTER AND MASONRY - Cure for 30 days before painting. "Slick poured" or pre-cast concrete needs chemical cleaning or a light sandblasting. Thoroughly rinse with water and

allow to fully dry. Remove loose aggregate and prime with a **GLIDDEN** primer. For concrete block, fill with a **GLIDDEN** block filler.

STEEL, GALVANIZED METAL AND ALUMINUM - Clean off oils, then prime with a **GLIDDEN** primer.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear an NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

DIRECTIONS FOR USE

QUALITY TOOLS FOR A QUALITY JOB

Use a 3/8" - 1/2" nap roller and a nylon or polyester brush/paint pad.

LET'S GET PAINTING

Mix thoroughly • Apply at package consistency or thin only when using a sprayer - use 1/2 pint water per gallon • Apply generously, no overspreading • Certain colors may require more than one coat for complete hide • Ventilate & provide warmth for normal drying.

4. Stir with a lifting motion for uniform color.
5. Dampen roller slightly with water.

1. Brush/Edge a 3"- 4" border on wall around all edges.
2. In small sections, spread paint in a W pattern, then fill in with long, even strokes in the same direction.
3. Paint woodwork last with even strokes; paint away from the wet edge.

LET'S CLEAN UP

Clean hands and tools with warm, soapy water • Clean spills right away with a damp cloth • When paint has fully cured, typically after 30 days, areas may be washed with a non-abrasive, mild detergent.

PRECAUTIONS

WARNING! CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION. CONTAINS CRYSTALLINE SILICA WHICH CAN CAUSE LUNG CANCER AND OTHER LUNG DAMAGE IF INHALED. MAY BE HARMFUL IF SWALLOWED. WHEN TINTED, CONTAINS ETHYLENE GLYCOL WHICH CAN CAUSE SEVERE KIDNEY DAMAGE WHEN INGESTED AND HAS BEEN SHOWN TO CAUSE BIRTH DEFECTS IN LABORATORY ANIMALS. USE ONLY WITH ADEQUATE VENTILATION. KEEP OUT OF THE REACH OF CHILDREN. For emergency information call (800) 545-2643. **Note:** These warnings encompass the product series. Prior to use, read and follow product-specific MSDS and label information. If sanding, wear a dust mask to avoid breathing of sanding dust. Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. Avoid contact with eyes and skin. If you experience eye watering, headaches, or dizziness, leave the area. If properly used, a respirator may offer additional protection. Obtain professional advice before using. Close container after each use. **FIRST AID:** For skin contact, wash thoroughly with soap and water. If any product remains, gently rub with petroleum jelly, vegetable or mineral/baby oil then wash again with soap and water. Repeat as needed. Remove contaminated clothing. For eye contact, flush immediately with plenty of water for at least 15 minutes. **Get medical attention.** If swallowed, **get medical attention immediately.** If inhalation causes discomfort, remove to fresh air. If discomfort persists or breathing difficulty occurs, get medical attention. **KEEP FROM FREEZING.**

DS4-1105

SHIPPING

FREIGHT CLASSIFICATION:
Paint. Freezable

PACKAGING:
4 quart (0.946 L)
1 gallon (3.785 L)
5 gallon (18.925 L)

FLASH POINT:
None



ICI Paints, Strongsville, Ohio 44136



1-800-GLIDDEN • www.glidden.com

LIMITATION OF LIABILITY To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance but are subject to change without prior notice. We guarantee our product to conform to the specifications contained herein. WE MAKE NO OTHER WARRANTY OR GUARANTEE OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY AND FITNESS FOR PARTICULAR PURPOSE. Liability, if any, is limited to replacement of the product or refund of the purchase price. LABOR OR COST OF LABOR AND OTHER CONSEQUENTIAL DAMAGES ARE HEREBY EXCLUDED.