



Date Issued 12/05/90
Supersedes: 09/07/89

TEXACO
MATERIAL SAFETY DATA SHEET

NOTE: Read and understand Material Safety Data Sheet before handling or disposing of product

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MATERIAL IDENTITY

Product Code and Name:

00707 REGAL OIL R&O N-100

Chemical Name and/or Family or Description:
Turbine Oils

Manufacturer's Name and Address:

Texaco Lubricants Co. Div of TRMI
P.O. Box 52332 Houston, TX 77052

Telephone Numbers

TRANSPORTATION EMERGENCY Company: (914) 831-3400

CHEMTREC: (800) 424-9000

HEALTH EMERGENCY Company: (914) 831-3400

GENERAL MSDS ASSISTANCE (914) 838-7204

TECHNICAL INFORMATION Fuels: (914) 838-7326; Lubricants/Antifreezes: (914) 838-7326
Chemicals: (512) 455-6543

2. COMPOSITION/INFORMATION ON INGREDIENTS

Product and/or Component(s) Carcinogenic According to:

OSHA	IARC	NTP	OTHER	NONE
-	-	-	-	?

Composition:

Chemical/Common Name

CAS No.

Exposure Limit

Pure in %

Severely refined hydrotreated heavy naph-
thenic petroleum distillates

64742525

5mg/m3 OSHA (MIST)
5mg/m3 ACGIH (MIST)
10mg/m3 STEL (MIST)

95.00 - 99.99

Product is non-hazardous according to OSHA (1910.1200).

3. HAZARD IDENTIFICATION

EMERGENCY OVERVIEW

Appearance and Odor: Light pale liquid

WARNING STATEMENT

NONE CONSIDERED NECESSARY

HMIS
Health: 0
Flammability: 1

Reactivity: 0
Special: -

NFPA
Health: 0
Flammability: 1
Reactivity: 0
Special: -

POTENTIAL HEALTH EFFECTS

Primary Route of Exposure:
Effects of Overexposure

EYE SKIN INHALATION INGESTION
☒ ☒ ☒ -

Acute

Eyes:

May cause minimal irritation, experienced as temporary discomfort.

Skin:

No adverse effects expected from absorption of material through the skin.

Brief contact is not irritating. Prolonged contact, as with clothing wetted with material, may cause defatting of skin or irritation, seen as local redness with possible mild discomfort



PRODUCT CODE: 00707
PRODUCT NAME: REGAL OIL R&D N-100

Date Issued: 12/05/90
Supersedes: 09/07/89

3. HAZARD IDENTIFICATION (CONT)

Inhalation:

Vapors or mist, in excess of permissible concentrations, or in unusually high concentrations generated from spraying, heating the material or as from exposure in poorly ventilated areas or confined spaces, may cause irritation of the nose and throat, headache, nausea, and drowsiness.

Ingestion:

No adverse effects expected. If more than several mouthfuls are swallowed, abdominal discomfort, nausea, and diarrhea may occur.

Sensitization Properties:

Unknown.

Chronic:

No adverse effects anticipated.

Medical Conditions Aggravated by Exposure:

Because of its derallting properties, prolonged and repeated skin contact may aggravate an existing dermatitis (skin condition).

Other Remarks:

None

4. FIRST AID MEASURES

Eyes:

Flush eyes with plenty of water for several minutes. Get medical attention if eye irritation persists.

Skin:

Wash skin with plenty of soap and water for several minutes. Get medical attention if skin irritation develops or persists.

Ingestion:

If more than several mouthfuls have been swallowed, give two glasses of water (16 oz.). Get medical attention.

Inhalation:

If irritation, headache, nausea, or drowsiness occurs, remove to fresh air. Get medical attention if breathing becomes difficult or symptoms persist.

Other Instructions:

Remove and dry-clean or launder clothing soaked or soiled with this material before reuse. Dry cleaning of contaminated clothing may be more effective than normal laundering. Inform individuals responsible for cleaning of potential hazards associated with handling contaminated clothing.

5. FIRE-FIGHTING MEASURES

Ignition Temp. Degrees F.: N.D.
Flammable Limits (%) Lower: N.D.

Flash Point Degrees F. (Method): 385°F (COC)
Upper: N.D.

Recommended Fire Extinguishing Agents And Special Procedures:

According to NFPA Guide, use water spray, dry chemical, foam, or carbon dioxide. Water or foam may cause frothing. Use water to cool fire-exposed containers. If a leak or spill has not ignited, use water spray to disperse the vapors and to provide protection for persons attempting to stop the leak.

Unusual or Explosive Hazards:

None



PRODUCT CODE: 00707
PRODUCT NAME: REGAL OIL R&O N-100

Date Issued: 12/05/90
Supersedes: 09/07/89

6. ACCIDENTAL RELEASE MEASURES (Transportation Spills Call: CHEMTREC (800) 424-9300)

Procedures in Case of Accidental Release, Breakage or Leakage:

Ventilate area. Avoid breathing vapor. Use self-contained breathing apparatus or supplied air for large spills or confined areas. Contain spill if possible. Wipe up or absorb on suitable material and shovel up. Prevent entry into sewers and waterways. Avoid contact with skin, eyes or clothing.

7. HANDLING AND STORAGE

Precautions to be Taken in Handling and Storage:

Minimum feasible handling temperatures should be maintained. Periods of exposure to high temperatures should be minimized. Water contamination should be avoided.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Protective Equipment (Type)

Eye/Face Protection:

Chemical-type goggles or face shield recommended to prevent eye contact.

Skin Protection:

Workers should wash exposed skin several times daily with soap and water. Soiled work clothing should be laundered or dry-cleaned at least once a week.

Respiratory Protection:

Airborne concentrations should be kept to lowest levels possible. If vapor, mist or dust is generated, use respirator approved by MSHA or NIOSH as appropriate. Supplied air respiratory protection should be used for cleaning large spills or upon entry into tanks, vessels, or other confined spaces. See below for applicable permissible concentrations.

Ventilation:

Adequate to meet component occupational exposure limits (see Section 2).

Exposure Limit for Total Product:

None established for this product; refer to Section 2 for component permissible concentration.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance and Odor: light pale liquid
Boiling Point (Degrees F.): N.D.
Specific Gravity: .9159 (H2O=1)
pH of undiluted product: N.A.
Vapor Pressure: N.D. mmHg
Viscosity: 93.3 cSt @ 40°C

Percent VOC: 100
Vapor Density: N.D. Air=1
Solubility in Water: N.D.
Other: -

10. STABILITY AND REACTIVITY

This Material Reacts Violently With: (If others is checked below, see comments for details)

Air Water Heat Strong Oxidizers Others None of These

- - - Y - -

Comments:

None

Products Evolved When Subjected to Heat or Combustion:

Toxic levels of carbon monoxide, carbon dioxide, irritating aldehydes and ketones.

Page: 3

N.D. - Not Determined
< Less Than

N.A. - Not Applicable
> Greater Than

N.T. - Not Tested



PRODUCT CODE: 00707
PRODUCT NAME: REGAL OIL R&O N-100

Date Issued: 12/05/90
Supersedes: 09/07/89

10. STABILITY AND REACTIVITY (CONT)

	OCCUR	DO NOT OCCUR
Hazardous Polymerizations:	-	X

11. TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION (ANIMAL TOXICITY DATA)

Median Lethal Dose (LD50 LC50) (Species)

Oral: Similar product >10 g/kg (rat); practically non-toxic

Inhalation: N.D.

Dermal: Similar product >8 g/kg (rabbit); practically non-toxic

Irritation Index, Estimation of Irritation (Species)

Skin: Similar product 0.13/8.0 (rabbit); no appreciable effect

Eyes: Similar product 2.33/110 (rabbit); no appreciable effect

Sensitization: N.D.

Other:

None

12. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHODS

This product has been evaluated for RCRA characteristics and does not meet the criteria of a hazardous waste if discarded in its purchased form. Under RCRA, it is the responsibility of the user of the product to determine at the time of disposal, whether the product meets RCRA criteria for hazardous waste. This is because product uses, transformations, mixtures, processes, etc. may render the resulting materials hazardous.

REMARKS

None

13. TRANSPORT INFORMATION

TRANSPORTATION

DOT: PROPER SHIPPING NAME: N.D.

IMDG: PROPER SHIPPING NAME: N.D.

IATA: PROPER SHIPPING NAME: N.D.

TDG: PROPER SHIPPING NAME: N.D.

14. REGULATORY INFORMATION

A. SARA TITLE III

Title III Section 302/304 Extremely Hazardous Substance:

Component	CAS No.	Percent	RQ (lbs)	TPQ (lbs)
NONE				

CERCLA Section 102(a) Hazardous Substance

Component	CAS No.	Percent	RQ (lbs)
NONE			

Title III Section 311 Hazard Categorization

Acute Chronic Fire Pressure Reactive Not Applicable

- - - - - X

Title III Section 313 Toxic Chemicals

Component	CAS No.	Percent
NONE		



PRODUCT CODE: 00707
PRODUCT NAME: REGAL OIL R&U N-100

Date Issued: 12/05/90
Supersedes: 09/07/89

14. REGULATORY INFORMATION (CONT)

B. WHMIS CLASSIFICATION
Not Regulated

C. MICHIGAN CRITICAL MATERIALS
No critical materials present.

15. OTHER INFORMATION

None

THE INFORMATION CONTAINED HEREIN IS BELIEVED TO BE ACCURATE. IT IS PROVIDED INDEPENDENTLY OF ANY SALE OF THE PRODUCT FOR PURPOSE OF HAZARD COMMUNICATION AS PART OF TEXACO'S PRODUCT SAFETY PROGRAM. IT IS NOT INTENDED TO CONSTITUTE PERFORMANCE INFORMATION CONCERNING THE PRODUCT. NO EXPRESS WARRANTY, OR IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE IS MADE WITH RESPECT TO THE PRODUCT OR THE INFORMATION CONTAINED HEREIN. DATA SHEETS ARE AVAILABLE FOR ALL TEXACO PRODUCTS. YOU ARE URGED TO OBTAIN DATA SHEETS FOR ALL TEXACO PRODUCTS YOU BUY, PROCESS, USE OR DISTRIBUTE AND YOU ARE ENCOURAGED AND REQUESTED TO ADVISE THOSE WHO MAY COME IN CONTACT WITH SUCH PRODUCTS OF THE INFORMATION CONTAINED HEREIN.

TO DETERMINE APPLICABILITY OR EFFECT OF ANY LAW OR REGULATION WITH RESPECT TO THE PRODUCT, USER SHOULD CONSULT HIS LEGAL ADVISOR OR THE APPROPRIATE GOVERNMENT AGENCY. TEXACO DOES NOT UNDERTAKE TO FURNISH ADVICE ON SUCH MATTERS.

Date: 12-05-90 ☐ New ☒ Revised, Supersedes: 09-07-89
Date Printed: 01-08-91

Inquiries regarding MSDS should be directed to:
Texaco Inc.
Manager, Product Safety
P.O. Box 509
Beacon, N.Y. 12508

PLEASE SEE NEXT PAGE FOR PRODUCT LABEL



PRODUCT CODE: 00707
PRODUCT NAME: REGAL OIL R&O N-100

Date issued: 12/05/90
Supersedes: 09/07/89

16. PRODUCT LABEL

READ AND UNDERSTAND MATERIAL SAFETY DATA SHEET BEFORE HANDLING OR DISPOSING OF PRODUCT

00707 REGAL OIL R&O N-100

WARNING STATEMENT

NONE CONSIDERED NECESSARY

PRECAUTIONARY MEASURES

AVOID PROLONGED BREATHING OF MIST OR VAPOR
WORKERS SHOULD WASH EXPOSED SKIN SEVERAL TIMES DAILY WITH SOAP
AND WATER

FIRST AID

INGESTION:

If more than several mouthfuls have been swallowed, give two glasses of water (16 oz.). Get medical attention.

INHALATION:

If irritation, headache, nausea, or drowsiness occurs, remove to fresh air. Get medical attention if breathing becomes difficult or symptoms persist.

EYE CONTACT:

Flush eyes with plenty of water for several minutes. Get medical attention if eye irritation persists.

SKIN CONTACT:

Wash skin with plenty of soap and water for several minutes. Get medical attention if skin irritation develops or persists.

FIRE

In case of fire, use foam, dry chemical, or CO2. Use water spray to keep containers cool.

Chemical/Common Name	CAS No.	Range in %
Severely refined hydrotreated heavy naph- thenic petroleum distillates	64742525	95.00 - 99.99

Product is non-hazardous according to OSHA (1910.1200).
Not classified as a hazardous material by DOT definition.

HMIS

Health : 0 Reactivity : 0
Flammability: 1 Special : -

National Fire Protection Association

Health : 0 Reactivity : 0
Flammability: 1 Special : -

CAUTION: Misuse of empty containers can be hazardous. Empty containers can be hazardous if used to store toxic, flammable, or reactive materials. Cutting or welding of empty containers might cause fire, explosion or toxic fumes from residues. Do not pressurize or expose to open flame or heat. Keep container closed and drum bungs in place.

Manufacturer's Name: Texaco Lubricants Co. Div of TRMI
P.O. Box 52332 Houston, TX 77052

TRANSPORTATION EMERGENCY Company: (914) 831-3400
CHEMTREC. (800) 424-9300

HEALTH EMERGENCY Company: (914) 831-3400